

PRODUCT MODEL

Catalog # 9075020

WaterPro RO System



All Features & Specifications

Features

- Timed dispense from 1 to 99.9 minutes for unattended operation
- Large capacity white polypropylene bowls with threaded heads
- Integral 17 liter polyethylene storage tank
- Attractive and durable Type 304 stainless steel front panel; epoxy-coated steel cabinet
- Temperature compensated conductivity LED monitor displays water quality in microsiemens from 1 to 999.
- Quiet 1/4 hp motor/rotary vane pump
- Storage tank air vent filter removes bacteria, maintaining water quality.
- Automatic flush valve extends RO membrane life by automatically flushing the RO membrane and tank for 3 minutes after each 12 hour period of inactivity.
- Internal pressure gauge monitors and displays RO-purified water pressure from 0 to 160 psi.
- Dispensing valve

- Wall mountable
- ETL listed

Options

- International electrical configuration

Required Accessories

- Prefilter/Carbon Filter Kit
- Reverse Osmosis Membrane

Optional Accessories

- WaterPro RO/PS Electrical Connection Cord
- WaterPro RO/PS Mobile Stand
- Support Stand
- Dispensing Gun
- 70 Liter Storage Tanks

Specifications

Weight	90.0
Dimensions	31.1"w x 7.6"d x 30.8"h
Electrical	115 volts, 60 Hz, 12 amps, Domestic
Height	0
Shipping Length	0
Metric Weight (kg)	41.0
Width	0
Feedwater Sources	Tap Water
Flow Rate	1.1 Liters Per Minute

Power Cord and Plug	North America, 115 Volts, 15 Amps
Service Fixtures	None
Water Purity Desired	Type III
Conformance	CE, ETI
Purification Method	Carbon Filtration, Reverse Osmosis
Required Accessories	Prefilter/carbon Filter Kit, Reverse Osmosis Membrane
