

Thermo Scientific RT Basic Series Magnetic Stirrers

Experience the reliability of our plug-and-play stirrers, ideal for routine stirring applications.



FEATURES

- Strong magnetic coupling to ensure consistent stirring during experimental procedures
- Three size options
- Low profile lightweight design with small footprint
- Speed Control: 150 to 2500rpm
- Two non-slip silicone plate covers provided with all units (1 black, 1 white)



3

Ordering Information and Specifications

| Cat. No. | 88880007 | 88880008 | 88880009 | 88880010 | 88880011 | 88880012 |
|--------------------------------------|--|----------|--|----------|--|----------|
| Plug Configuration | | | | | | |
| Mechanism | Brushless DC motor | | Brushless DC motor | | Brushless DC motor | |
| Stirring Capacity (H ₂ O) | 2L | | 4L | | 5L | |
| Speed Range | 150 to 2500rpm | | 150 to 2500rpm | | 150 to 2500rpm | |
| Maximum Load (vessel) | 15kg / 33.07lbs | | 20kg / 44.09lbs | | 25kg / 55.12lbs | |
| Body Material | Polypropylene | | Polypropylene | | Polypropylene | |
| Top Plate Dimensions | 120mm / 4.72in diameter | | 170mm / 6.69in diameter | | 220mm / 8.66in diameter | |
| Overall Dimensions (WxDxH) | 130 x 130 x 65mm 5.12 x 5.12 x 2.56in | | 185 x 185 x 65mm 7.28 x 7.28 x 2.56in | | 230 x 230 x 65mm 9.06 x 9.06 x 2.56in | |
| Power Consumption | 5W | | 6W | | 6W | |
| Power | 100 – 240V, 50/60Hz | | 100 – 240V, 50/60Hz | | 100 – 240V, 50/60Hz | |
| Certifications | CE | | CE | | CE | |
| Warranty | 2 Years | | 2 Years | | 2 Years | |

Accessories for RT Basic Series Magnetic Stirrers

| | Cat. No. |
|--|-----------------|
| Non-slip silicone plate cover for items 88880007 and 88880008 (White color, Silicone Ø120cm) | 88880144 |
| Non-slip silicone plate cover for items 88880009 and 88880010 (White color, Silicone Ø170cm) | 88880145 |
| Non-slip silicone plate cover for items 88880011 and 88880012 (White color, Silicone Ø220cm) | 88880146 |



Non-slip Silicone Plate Covers