

ARG2PV-CRTLHD



22.25" x 18.5" x 23.25" (H x W x D)

Performance series 2 cu.ft. countertop glass door controlled room temperature cabinet for pharmaceuticals and vaccines in a white finish with lock and antimicrobial silver-ion handle

Highlights:

Adjustable operating control range from 68 to 77°F (preset to 72°F)

Controlled room temperature cabinet to store medication, pharmaceuticals, and other sensitive materials at 72°F

Intelligent microprocessor digital temperature controller

Product Features:

| | |
|---|---|
| Controlled Room Temperature Cabinet | Purpose-built design to store medication, pharmaceuticals, and other sensitive materials at 72°F |
| Purpose-built design | Designed and purpose-built to support manufacturer recommendations for storage of pharmacy, medication, and vaccines within 20° - 25°C (68° - 77°F) as defined by USP 1079> Good Storage and Distribution Practices for Drug Products |
| +/-1.5°C Variation | The published temperature variation is derived from the maximum deviation of an NTC sensor in a 1 oz. vial located nearest the chamber geometric center during a 24 hour test period |
| Stable operation | Designed to maintain a set temperature, even when ambient room temperature is as cold as 68°F or as high as 86°F |
| Antimicrobial silver ion-coated handle | Powder-coated handle with naturally occurring silver ions to help reduce germ spread |
| Adjustable temperature | Intuitive controls let you adjust the interior temperature between +68 to +77°F |
| Temperature alarm | Visual and audible alarms alert if the interior temperature rises or falls out of set range |
| Remote alarm contacts | Electronic controller is equipped with a volt-free contact for alarm forwarding to an external remote system (contacts located in the external rear of the unit) |
| Automatic defrost with adjustable cycle | Adjustable cycle defrost operation ensures the unit avoid temperature spikes and ice buildup |

ARG2PV-CRTLHD Specifications:

| Overview | |
|----------------------------|-----------------------------|
| Height of Cabinet | 22.25" (57 cm) |
| Width | 18.5" (47 cm) |
| Width with Door Open | 18.88" (48 cm) |
| Depth | 23.25" (59 cm) |
| Depth with Handle | 24.75" (63 cm) |
| Depth with door at 90° | 42.5" (108 cm) |
| Capacity | 1.94 cu.ft. (55 L) |
| Defrost Type | Automatic |
| Door | Glass |
| Cabinet | White |
| US Electrical Safety | ETL |
| Canadian Electrical Safety | ETL-C |
| Amps | 0.6 |
| Voltage/Frequency | 115 V AC/60 Hz |
| Weight | 80.0 lbs. (36 kg) |
| Shipping Weight | 104.0 lbs. (47 kg) |
| Parts & Labor Warranty | 2 Years |
| Compressor Warranty | 5 Years |
| UPC | 761101107028 |
| Refrigerator Features | |
| Door Swing | LHD |
| Reversible | No |
| Shelf Type | Wire |
| Shelf Qty | 2 |
| Adjustable Shelves | Yes |
| Thermostat Type | Digital |
| Fan Type | Interior |
| Refrigerant Type | R600a |
| Refrigerant Amount | 0.84oz. |
| High Side PSI | 280.0 |
| Low Side PSI | 90.0 |
| Interior Light | Yes |
| Temperature Range | 68 to 77°F (preset to 72°F) |
| Sound Level | 42.4 dB |

| Dimensions | |
|------------------------|----------------|
| Interior Height | 16.5" (42 cm) |
| Interior Width | 15.25" (39 cm) |
| Interior Depth | 15.75" (40 cm) |
| Compressor Step Height | 8.25" (21 cm) |
| Compressor Step Width | 15.25" (39 cm) |
| Compressor Step Depth | 4.25" (11 cm) |

