

Specifications

4" X 4"

Model Number	SP131015	SP131010-33	SP131014
Overall Dimensions in. (cm)			
Width	5.0" (12.7 cm)	5.0" (12.7 cm)	5.0" (12.7 cm)
Height	3.6" (9.7 cm)	3.6" (9.7 cm)	3.6" (9.7 cm)
Depth	10.0" (25.4 cm)	10.0" (25.4 cm)	10.0" (25.4 cm)
Weight lbs (kg)	7.0 lbs (3.2 kg)	7.0 lbs (3.2 kg)	7.0 lbs (3.2 kg)
Top Plate			
Width	4.25" (10.8 cm)	4.25" (10.8 cm)	4.25" (10.8 cm)
Height	1.0" (2.5 cm)	1.0" (2.5 cm)	1.0" (2.5 cm)
Depth	4.25" (10.8 cm)	4.25" (10.8 cm)	4.25" (10.8 cm)
Electrical Ratings			
Volts	120	220-240	100
Amps	3.3	1.8	4.1
Watts	395	440	410
Freq.	60	50/60	50/60
Phase	1	1	1
Max. Temp. °F (°C)	1004°F (540°C)	1004°F (540°C)	1004°F (540°C)

7" X 7"

Model Number	SP131325	SP131320-33	SP131324
Overall Dimensions in. (cm)			
Width	8.2" (20.8 cm)	8.2" (20.8 cm)	8.2" (20.8 cm)
Height	3.8" (9.7 cm)	3.8" (9.7 cm)	3.8" (9.7 cm)
Depth	13.0" (33.0 cm)	13.0" (33.0 cm)	13.0" (33.0 cm)
Weight lbs (kg)	11.0 lbs (5.0 kg)	11.0 lbs (5.0 kg)	11.0 lbs (5.0 kg)
Top Plate			
Width	7.25" (18.4 cm)	7.25" (18.4 cm)	7.25" (18.4 cm)
Height	1.0" (2.5 cm)	1.0" (2.5 cm)	1.0" (2.5 cm)
Depth	7.25" (18.4 cm)	7.25" (18.4 cm)	7.25" (18.4 cm)
Electrical Ratings			
Volts	120	220-240	100
Amps	8.9	4.9	11.0
Watts	1070	1170	1095
Freq.	60	50/60	50/60
Phase	1	1	1
Max. Temp. °F (°C)	1004°F (540°C)	1004°F (540°C)	1004°F (540°C)

10" X 10"

Model Number	SP131635	SP131630-33	SP131634
Overall Dimensions in. (cm)			
Width	11.38" (28.9 cm)	11.38" (28.9 cm)	11.38" (28.9 cm)
Height	4.0" (10.2 cm)	4.0" (10.2 cm)	4.0" (10.2 cm)
Depth	16.25" (41.3 cm)	16.25" (41.3 cm)	16.25" (41.3 cm)
Weight lbs (kg)	13.75 lbs. (6.24 kg)	13.75 lbs. (6.24 kg)	13.75 lbs. (6.24 kg)
Top Plate			
Width	10.5" (26.7 cm)	10.5" (26.7 cm)	10.5" (26.7 cm)
Height	1.0" (2.5 cm)	1.0" (2.5 cm)	1.0" (2.5 cm)
Depth	10.5" (26.7 cm)	10.5" (26.7 cm)	10.5" (26.7 cm)
Electrical Ratings			
Volts	120	220-240	100
Amps	12	6.5	11.5
Watts	1440	1550	1150
Freq.	60	50/60	50/60
Phase	1	1	1
Max. Temp. °F (°C)	750°F (400°C)	750°F (400°C)	750°F (400°C)