




SAMPLE DIVIDER PT 100

A faultless and comparable analysis is closely linked to **accurate sample handling**. Only a sample representative of the initial material can provide **meaningful analysis results**. Rotating dividers ensure the **representativeness** of a sample and thus the **reproducibility of the analysis**.

The sample divider PT 100 divides the sample so exactly that the **composition of each fraction of the sample corresponds exactly to that of the original bulk sample**. This applies both for fine-powdered and coarse materials. The material feed and dividing processes take place **automatically, without interruption and without loss of material**. The Sample Divider PT 100 has a **modular design** and can be put together to suit individual requirements. It offers an **extremely flexible** range of possible applications. A feeder, various dividing heads, sample receptacle vessels and further useful accessories are available in addition to the drive unit.



[Click to view video](#)

PRODUCT ADVANTAGES


- | high division accuracy to suit modern analytical devices
- | modular design
- | automatic material feed via synchronized feeder
- | quick-release clamping system for simple and rapid handling of sample bottles
- | digital time setting
- | speed is monitored and kept constant
- | wide range of accessories including various dividing heads, collection and feeding systems
- | compact, easy to clean

APPLICATION EXAMPLES

cement clinker, chemicals, coffee, construction materials, fertilizers, fillers, flours, grains, metals powders, minerals, nuts, sand, seeds, soils, washing powder, ...

FUNCTIONAL PRINCIPLE

The material to be divided first flows through a decentrally located feed hopper. The material first flows through a feed hopper - which is located off-center - directly into the openings of the dividing head. This procedure results in very small, and therefore neglectable, deviations between the part samples in the sample bottles, even with coarse materials. The dividing process itself runs automatically and tamper-proof. The speed-controlled dividing head rotates at a constant 110 revolutions per minute, independent of the load and the mains frequency. This means that when using a dividing head with ten outlets, the feed flow is divided into 1100 individual samples each minute, thus providing optimum dividing accuracy. The dividing heads divide the material evenly among the sample bottles which are available in various sizes.



[Click to view video](#)

SAMPLE DIVIDER PT 100

TECHNICAL DATA

Applications	sample division, sample reduction
Field of application	agriculture, biology, chemistry / plastics, construction materials, engineering / electronics, environment / recycling, food, geology / metallurgy, glass / ceramics, medicine / pharmaceuticals
Feed material	bulk materials
Material feed size*	<= 10 mm
Batch size / feed quantity*	<= 5000 ml
Rotary speed	110 min ⁻¹
Number of divisions	6 / 8 / 10
Time setting	digital, 1, 3, 5, 10 - 60 min / continuous operation
Container volume	30 ml / 100 ml / 250 ml / 500 ml
Electrical supply data	100-240 V, 50/60Hz
Power connection	1-phase
W x H x D	580 x 910 x 420 mm (incl. DR 100)
Net weight	~ 33.5 kg (incl. DR 100)
Standards	CE

*depending on feed material and instrument configuration/settings

www.retsch.com/pt100

ORDER DATA

SAMPLE DIVIDER PT 100

PT 100 drive unit

(please order vibratory feeder, feeding kit, dividing head and sample bottles separately)

40.535.0001



PT 100 drive unit

100–240 V, 50/60 Hz

DIVIDING HEADS FOR FEED SIZES UP TO 10 MM

42.793.0003



Dividing head of aluminum hard anodized, GL 55 thread with 6 quick-release sample outlets

42.793.0001



Dividing head of aluminum hard anodized, GL 55 thread with 8 quick-release sample outlets

42.793.0002



Dividing head of aluminum hard anodized, GL 55 thread with 10 quick-release sample outlets

42.793.0007



Dividing head of POM, GL 55 thread with 8 quick-release sample outlets

22.523.0001



Sample bottles, GL 55 thread, 250 ml, 10 pieces

22.523.0002



Sample bottles, GL 55 thread, 500 ml, 10 pieces

DIVIDING HEADS FOR FEED SIZES UP TO 5 MM

42.793.0009



Dividing head of aluminum hard anodized, GL 45 thread with 8 quick-release sample outlets

22.523.0003



Duran laboratory bottles, GL 45 thread, 100 ml, 10 pieces for dividing head 42.793.0009

22.523.0004



Duran laboratory bottles, GL 45 thread, 250 ml, 10 pieces for dividing head 42.793.0009

22.523.0005




Duran laboratory bottles, GL 45 thread, 500 ml, 10 pieces for dividing head 42.793.0009

42.018.0001  Support with beakers 30 ml and lids for dividing head 42.793.0009

42.156.0001  Spare beaker with lid 30 ml, 10 pcs.

ACCESSORIES PT 100

03.785.0146  Hopper, stainless steel, volume 2.8 l (for PT 100 used without DR 100)


03.742.0013  Protective dust cap for hopper, of POM

99.200.0015 IQ/OQ Documentation for PT 100

VIBRATORY FEEDER DR 100 FOR PT 100

DR 100 drive unit (please order feeding kit separately)

70.938.0001  DR 100 drive unit 220–240 V, 50 Hz

70.938.0002  DR 100 drive unit 110–120 V, 60 Hz

72.020.0021 Feeding kit DR 100-75/40 for PT 100, incl. push-fit feed chute 75/40 mm, holder for push-fit feed chute, hopper 3.5 litres, fixture for hopper and stand with data cable