

SPECIFICATIONS

Type Output:	Constant Voltage or Constant Millamps with automatic crossover
Maximum Voltage:	250 Volts
Maximum Current:	500 Millamps
Maximum Power:	125 Watts
Regulation:	≤ 1%
Accuracy:	± 1.5 % full scale for each display
Number of Output Terminals:	Four sets of recessed 4mm output connectors
Safety Interlock:	Load sensing shut-down-on disconnect. Key actuation necessary to begin voltage generation. In the event of shutdown due to power interruption, automatic restart is provided.
Timer:	0.00 to 24 hrs 00 min.
Input Power:	110 Volts or 240 Volts AC, 50/60 Hertz, 250 Watts
Ambient Operating Temperature Range:	0°C - 30°C (non-condensing atmosphere)
Dimensions:	7.5" (D) x 8.75" (W) x 5.5" (H) 19cm x 22cm x 14cm
Weight: (net) (shipping)	11 lbs 5 kg 15 lbs 6.8 kg

WARRANTY

This laboratory equipment was produced by Thermo Electron with the highest practical standards of materials, workmanship, and design. The design and manufacture of parts have been conceived with one purpose — to produce a unit which will give satisfactory service.

Thermo Electron guarantees this unit to be free from defects in materials or workmanship under normal use or service for four years from date of shipment.

If, during this time, this unit proves defective in materials or workmanship, the Company will repair or replace it free of charge if returned to us prepaid. This guarantee does not cover damage in transit, damage caused by carelessness, misuse or neglect, or unsatisfactory performance as a result of conditions beyond our control or consequential losses as a result of our product.

SERVICE

 **WARNING:** This notice alerts you to a potentially dangerous situation.

 **AVERTISSEMENT:** Cette notice attire votre attention sur des dangers potentiels.

This power supply is not equipped with any user serviceable parts except for the fuse.

Contact Thermo Electron or your local distributor for technical assistance if problems arise. The telephone number is (508) 482-7000, or (800) 327-2643.