

Performance Specifications

Performance Specifications (G1311B)

Table 4 Performance Specification Agilent 1260 Infinity Quaternary Pump (G1311B)

Type	Specification
Hydraulic system	Dual piston in series pump with proprietary servo-controlled variable stroke drive, floating pistons
Setable flow range	0.001 – 10 mL/min, in 0.001 mL/min increments
Flow range	0.2 – 10.0 mL/min
Flow precision	< 0.07 % RSD, or < 0.02 min SD whatever is greater, based on retention time at constant room temperature
Flow accuracy	± 1 % or 10 µL/min whatever is greater, pumping degassed H ₂ O at 10 MPa
Pressure	Operating range 0 – 60 MPa (0 – 600 bar, 0 – 8700 psi) up to 5 mL/min Operating range 0 – 20 MPa (0 – 200 bar, 0 – 2950 psi) up to 10 mL/min
Pressure pulsation	< 2 % amplitude (typically < 1.3 %), or < 3 bar at 1 mL/min isopropanol, at all pressures > 10 bar (147 psi)
Compressibility compensation	User-selectable, based on mobile phase compressibility
Recommended pH range	1.0 – 12.5, solvents with pH < 2.3 should not contain acids which attack stainless steel
Gradient formation	Low pressure quaternary mixing/gradient capability using proprietary high-speed proportioning valve
Delay volume	600 – 800 µL, dependent on back pressure
Composition range	0 – 95 % or 5 – 100 %, user selectable
Composition precision	< 0.2 % RSD, or < 0.04 min SD whatever is greater, at 0.2 and 1 mL/min
Control and data evaluation	Agilent control software

Table 4 Performance Specification Agilent 1260 Infinity Quaternary Pump (G1311B)

Analog output	For pressure monitoring, 1.33 mV/bar, one output
Communications	Controller-area network (CAN), RS-232C, APG Remote: ready, start, stop and shut-down signals, LAN optional

Performance Specifications (G1316A)

Table 5 Performance Specifications Thermostatted Column Compartment

Type	Specification	Comments
Temperature range	10 degrees below ambient to 80 °C up to 80 °C: flow rates up to 5 mL/min	
Temperature stability	± 0.15 °C	
Temperature accuracy	± 0.8 °C ± 0.5 °C	With calibration
Column capacity	Three 30 cm	
Warm-up/cool-down time	5 minutes from ambient to 40 °C 10 minutes from 40 – 20 °C	
Dead volume	3 µL left heat exchanger 6 µL right heat exchanger	
Communications	Controller-area network (CAN), RS-232C, APG Remote: ready, start, stop and shut-down signals, LAN via other 1260 Infinity module	
Safety and maintenance	Extensive diagnostics, error detection and display (through Instant Pilot and Agilent data system), leak detection, safe leak handling, leak output signal for shutdown of pumping system. Low voltages in major maintenance areas.	
GLP features	Column-identification module for GLP documentation of column type.	
Housing	All materials recyclable	

Performance Specifications (G1329B)

Table 6 Performance Specifications Agilent 1260 Infinity Standard Autosampler (G1329B)

Type	Specification
Pressure	Operating range 0 - 60 MPa (0 - 600 bar, 0 - 8850 psi)
GLP features	Early maintenance feedback (EMF), electronic records of maintenance and errors
Communications	Controller-area network (CAN), GPIB (IEEE-448), RS232C, APG-remote standard, optional four external contact closures and BCD vial number output
Safety features	Leak detection and safe leak handling, low voltages in maintenance areas, error detection and display
Injection range	0.1 - 100 μ L in 0.1 μ L increments (recommended 1 μ L increments) Up to 1500 μ L with multiple draw (hardware modification required)
Replicate injections	1 – 99 from one vial
Precision	Typically < 0.25 % RSD of peak areas from 5 - 100 μ L, Typically < 1 % RSD of peak areas from 1 - 5 μ L,
Minimum sample volume	1 μ L from 5 μ L sample in 100 μ L microvial, or 1 μ L from 10 μ L sample in 300 μ L microvial
Carryover	Typically < 0.1 %, < 0.05 % with external needle cleaning
Sample viscosity range	0.2 – 50 cp
Sample capacity	100 \times 2 mL vials in 1 tray 40 \times 2 mL vials in 1/2 tray 15 \times 6 mL vials in 1/2 tray (Agilent vials only)
Injection cycle time	50 s for draw speed 200 μ L/min, ejection speed 200 μ L/min, injection volume 5 μ L

Performance Specifications

Table 2 Performance specifications Agilent 1290 Infinity Thermostat

Type	Specification
Temperature range	Settable from 4 °C to 40 °C in 1 ° increments
Temperature accuracy at ambient temperatures < 25 °C and humidity < 50 %	3 °C to 8 °C at a setpoint of 4 °C*
Temperature accuracy at ambient temperatures <30 °C and humidity <60 %	3 °C to 9 °C at a setpoint of 4 °C*

* Measurement conditions:

G1329B:

with 100-Vial Tray in vial location 2,10,92 and 100 vials filled with water

G1367A/G1367B/G1367C/G1377A/G1367E/G5667A/G2258A/G4226A:

For vials: Using the Thermostatable Tray (G1329-60011) or 100 Micro-Vial (G4226-60021), both loaded with 100 vials. Temperature is measured in vial locations 1,10,23,25,45,75,91 and 100 (filled with 1 mL of water)

For well plates: Standard Tray (G2258-60011) for two Well Plates loaded with two Agilent 96 Well Plate (5042-1386)

Performance Specifications

Specifications

Performance Specifications G1315C

Table 3 Performance Specifications G1315C

Type	Specification	Comments
Detection type	1024-element photodiode array	
Light source	Deuterium and tungsten lamps	The UV-lamp is equipped with RFID tag that holds lamp typical information.
Data rate	up to 80 Hz	
Wavelength range	190 – 950 nm	
Short term noise (ASTM) Single and Multi-Wavelength	$< \pm 0.7 \cdot 10^{-5}$ AU at 254 and 750 nm	see " <i>Specification Conditions</i> " below
Drift	$< 0.9 \cdot 10^{-3}$ AU/h at 254 nm	see " <i>Specification Conditions</i> " below
Linear absorbance range	> 2 AU (5 %) at 265 nm	see " <i>Specification Conditions</i> " below
Wavelength accuracy	± 1 nm	Self-calibration with deuterium lines, verification with holmium oxide filter
Wavelength bunching	1 – 400 nm	Programmable in steps of 1 nm
Slit width	1, 2, 4, 8, 16 nm	Programmable slit
Diode width	< 1 nm	

Table 3 Performance Specifications G1315C

Type	Specification	Comments
Flow cells	<p>Standard: 13 μL volume, 10 mm cell path length and 120 bar (1740 psi) pressure maximum</p> <p>Standard bio-inert: 13 μL volume, 10 mm cell path length and 120 bar (1740 psi) pressure maximum</p> <p>Semi-micro: 5 μL volume, 6 mm cell path length and 120 bar (1740 psi) pressure maximum</p> <p>Micro: 2 μL volume, 3 mm cell path length, 120 bar (1740 psi) pressure maximum</p> <p>Semi-nano: 500 nL volume, 10 mm cell path length and 50 bar (725 psi) pressure maximum</p> <p>Nano: 80 nL volume, 6 mm cell path length and 50 bar (725 psi) pressure maximum</p> <p>High pressure: 1.7 μL volume, 6 mm cell path length and 400 bar (5800 psi) pressure maximum</p> <p>Prep SST: 3 mm cell path length and 120 bar (1740 psi) pressure maximum</p> <p>Prep Quartz: 0.3 mm cell path length and 20 bar (290 psi) pressure maximum</p> <p>Prep Quartz: 0.06 mm cell path length and 20 bar (290 psi) pressure maximum</p>	<p>All flow cells are equipped with RFID tags that hold cell typical information.</p> <p>pH range 1.0—9.5 (12.5 solvent dependent with bio-inert version)</p>
Time programmable	<p>Wavelength, polarity, peak width, lamp bandwidth, autobalance, wavelength range, threshold, spectra storage mode</p>	
Spectral tools	<p>Data analysis software for spectra evaluation, including spectral libraries and peak purity functions</p>	

Performance Specifications

Table 4 Performance Specifications Agilent 1260 Infinity Fluorescence Detector (G1321B)

Type	Specification	Comments
Detection type	Multi-signal fluorescence detector with rapid on-line scanning capabilities and spectral data analysis	
Performance specifications	<p>Single wavelength operation:</p> <ul style="list-style-type: none"> • RAMAN (H₂O) > 500 (noise reference measured at signal) Ex=350 nm, Em=397 nm, dark value 450 nm, standard flow cell • RAMAN (H₂O) > 3000 (noise reference measured at dark value) Ex=350 nm, Em=397 nm, dark value 450 nm, standard flow cell <p>Dual wavelength operation: RAMAN (H₂O) > 300 Ex 350 nm, Em 397 nm and Ex 350 nm, Em 450 nm, standard flow cell.</p>	see note below this table see Service Manual for details
Light source	Xenon Flash Lamp, normal mode 20 W, economy mode 5 W, lifetime 4000 h	
Pulse frequency	296 Hz for single signal mode 74 Hz for economy mode	
Maximum data rate	74 Hz, 145 Hz	145 Hz with firmware A.06.54 and above
Excitation monochromator	Range: settable 200 nm - 1200 nm and zero-order Bandwidth: 20 nm (fixed) Monochromator: concave holographic grating, F/1.6, blaze: 300 nm	

Table 4 Performance Specifications Agilent 1260 Infinity Fluorescence Detector (G1321B)

Type	Specification	Comments
Emission monochromator	Range: settable 200 nm - 1200 nm and zero-order Bandwidth: 20 nm (fixed) Monochromator: concave holographic grating, F/1.6, blaze: 400 nm	
Reference system	in-line excitation measurement	
Timetable programing	up to 4 signal wavelengths, response time, PMT Gain, baseline behavior (append, free, zero), spectral parameters	
Spectrum acquisition	Excitation or Emission spectra Scan speed: 28 ms per datapoint (e.g. 0.6 s/spectrum 200 – 400 nm, 10 nm step) Step size: 1 – 20 nm Spectra storage: All	
Wavelength characteristic	Repeatability +/- 0.2 nm Accuracy +/- 3 nm setting	
Flow cells	Standard: 8 µL volume and 20 bar (2 MPa) pressure maximum, fused silica block Optional: <ul style="list-style-type: none"> • Fluorescence cuvette for offline spectroscopic measurements with 1 mL syringe, 8 µL volume • Bio-inert: 8 µL volume and 20 bar (2 MPa) pressure maximum, (pH 1–12) • Micro: 4 µL volume and 20 bar (2 MPa) pressure maximum 	
Control and data evaluation	Agilent ChemStation for LC, Agilent Instant Pilot G4208A with limited spectral data analysis and printing of spectra	

2 Site Requirements and Specifications

Performance Specifications

Table 4 Performance Specifications Agilent 1260 Infinity Fluorescence Detector (G1321B)

Type	Specification	Comments
Analog outputs	Recorder/integrator: 100 mV or 1 V, output range > 100 LU, two outputs	100 LU is the recommended range, see <i>"FLD Scaling Range and Operating Conditions"</i>
Communications	Controller-area network (CAN), RS-232C, LAN, APG Remote: ready, start, stop and shut-down signals	
Safety and maintenance	Extensive support for troubleshooting and maintenance is provided by the Instant Pilot, Agilent Lab Advisor, and the Chromatography Data System. Safety-related features are leak detection, safe leak handling, leak output signal for shutdown of pumping system, and low voltages in major maintenance areas.	
GLP features	Early maintenance feedback (EMF) for continuous tracking of instrument usage in terms of lamp burn time with user-settable limits and feedback messages. Electronic records of maintenance and errors. Verification of wavelength accuracy, using the Raman band of water.	
Housing	All materials recyclable.	
Environment	0 – 40 °C constant temperature at <95 % humidity (non-condensing)	
Dimensions	140 mm x 345 mm x 435 mm (5.5 x 13.5 x 17 inches) (height x width x depth)	
Weight	11.5 kg (25.5 lbs)	