



Product specifications

Product specifications

Feature	Specifications
Input Power	115 VAC, 50/60 Hz 230 VAC, 50/60 Hz
Fuses	One T8A 250VAC, one extra fuse is provided
Output power in watts	350 W
Output voltage range	2 VDC - 300 VDC
Output current range	0.01 A – 3 A
Terminal pairs	4 (4 positive voltage and 4 negative voltage)
Operating Modes <ul style="list-style-type: none"> Constant Voltage Constant Current Constant Power 	<ul style="list-style-type: none"> 1 V step 1 mA step 1 watt step
Timer	Up to 999 min per step
Crossover	Automatic
Display type	Backlit TFT-LCD Graphic type
Display area	95 mm x 54 mm (W x H) (4.3 inch)
Display colors	16.7M colors
Pause function	Yes
Safety features	No Load Detection Load Change Detection Overload Detection Ground Leak Detection
Programmable	Yes <ul style="list-style-type: none"> Store up to 100 run methods Program up to 20 steps per method

(continued)

Feature	Specifications
Stackable	Yes
Housing material	Polycarbonate
Housing size	230 x 303 x 102 mm (W x D x H)
Operating temperature	0°C–40°C
Environmental conditions	≤95% RH (non-condensing), 75 KPa–106 KPa, altitude not to exceed 2,000 meters
Weight	2.4 kg
Certifications	CE, cTUVus, RCM, China RoHs
Warranty	1 year