

## Performance Specifications

**Table 2** Performance Specifications of the Agilent 1260 Infinity Binary Pump (G1312B)

Type	Specification	Comments
Hydraulic system	Two dual piston in series pumps with servo-controlled variable stroke drive, power transmission by gears and ball screws, floating pistons	
Setable flow range	Set points 0.001 – 5 mL/min, in 0.001 mL/min increments	
Flow range	0.05 – 5.0 mL/min	
Flow precision	≤0.07 % RSD or ≤0.02 min SD, whatever is greater	based on retention time at constant room temperature
Flow accuracy	± 1 % or 10 µL/min, what ever is greater	pumping degassed H <sub>2</sub> O at 10 MPa (100 bar)
Pressure operating range	Operating range 0 – 60 MPa (0 – 600 bar, 0 – 8700 psi) up to 5 mL/min	
Pressure pulsation	< 2 % amplitude (typically < 1.3 %), or < 0.3 MPa (3 bar), whatever is greater, at 1 mL/min isopropanol, at all pressures > 1 MPa (10 bar, 147 psi) <i>Low delay volume configuration:</i> < 5 % amplitude (typically < 2 %)	
Compressibility compensation	Pre-defined, based on mobile phase compressibility	
Recommended pH range	1.0 – 12.5, solvents with pH < 2.3 should not contain acids which attack stainless steel	
Gradient formation	High-pressure binary mixing	
Delay volume	<i>Standard delay volume configuration:</i> 600 – 800 µL, (includes 400 µL mixer), dependent on back pressure <i>Low delay volume configuration:</i> 120 µL	measured with water at 1 mL/min (water/caffeine tracer)

**Table 2** Performance Specifications of the Agilent 1260 Infinity Binary Pump (G1312B)

Type	Specification	Comments
Composition range	settable range: 0 – 100 % recommended range: 1 – 99 % or 5 µL/min per channel, whatever is greater	
Composition precision	< 0.15 % RSD or < 0.04 min SD whatever is greater	at 0.2 and 1 mL/min; based on retention time at constant room temperature
Composition accuracy	± 0.35 % absolute, at 2 mL/min, at 10 MPa (100 bar)	(water/cafeine tracer)
Control	Agilent control software (e.g. ChemStation, EZChrom, OL, MassHunter)	
Local control	Agilent Instant Pilot	Revision B.02.00 or above
Analog output	For pressure monitoring, 1.33 mV/bar, one output	
Communications	Controller-area network (CAN), RS-232C, APG Remote: ready, start, stop and shut-down signals, LAN optional	
Safety and maintenance	Extensive support for troubleshooting and maintenance is provided by the Instant Pilot, Agilent Lab Advisor, and the Chromatography Data System. Safety-related features are leak detection, safe leak handling, leak output signal for shutdown of pumping system, and low voltages in major maintenance areas.	
GLP features	Early maintenance feedback (EMF) for continuous tracking of instrument usage in terms of seal wear and volume of pumped mobile phase with pre-defined and user settable limits and feedback messages. Electronic records of maintenance and errors	
Housing	All materials are recyclable	

**NOTE**

For use with flow rates below 500 µl/min or for use without damper and mixer a vacuum degasser is required.

All specification measurements are done with degassed solvents.

## Performance Specifications Standard Autosampler

**Table 4** Performance Specifications Agilent 1260 Infinity Standard Autosampler (G1329B)

Type	Specification
Pressure	Operating range 0 - 60 MPa (0 - 600 bar, 0 - 8850 psi)
GLP features	Early maintenance feedback (EMF), electronic records of maintenance and errors
Communications	Controller-area network (CAN), RS232C, APG-remote standard, optional four external contact closures and BCD vial number output
Safety features	Leak detection and safe leak handling, low voltages in maintenance areas, error detection and display
Injection range	0.1 - 100 $\mu$ L in 0.1 $\mu$ L increments (recommended 1 $\mu$ L increments) Up to 1500 $\mu$ L with multiple draw (hardware modification required)
Replicate injections	1 – 99 from one vial
Precision	Typically < 0.25 % RSD of peak areas from < 5 $\mu$ L to 100 $\mu$ L Typically < 1 % RSD of peak areas from 1 $\mu$ L to 5 $\mu$ L
Minimum sample volume	1 $\mu$ L from 5 $\mu$ L sample in 100 $\mu$ L microvial, or 1 $\mu$ L from 10 $\mu$ L sample in 300 $\mu$ L microvial
Carryover	Typically < 0.1 %, < 0.05 % with external needle cleaning
Sample viscosity range	0.2 – 50 cp
Sample capacity	100 $\times$ 2 mL vials in 1 tray 40 $\times$ 2 mL vials in $\frac{1}{2}$ tray 15 $\times$ 6 mL vials in $\frac{1}{2}$ tray (Agilent vials only)
Injection cycle time	50 s for draw speed 200 $\mu$ L/min, ejection speed 200 $\mu$ L/min, injection volume 5 $\mu$ L
Metering device	Metering pump in high pressure flow path

# Performance Specifications

**Table 2**    Performance Specifications Agilent 1200 Series thermostatted autosampler

Type	Specification
Temperature range:	setable from 4 °C to 40 °C in 1 ° increments
Temperature accuracy at ambient temperatures < 25 °C and humidity < 50%	- 1°C to + 4 °C at a setpoint of 4 °C
Temperature accuracy at ambient temperatures > 25 °C and/or humidity > 50%	- 1°C to + 5 °C at a setpoint of 4 °C

## Performance Specifications

**Table 3** Performance Specifications Thermostatted Column Compartment

Type	Specification	Comments
Temperature range	10 degrees below ambient to 80 °C up to 80 °C: flow rates up to 5 mL/min	
Temperature stability	± 0.15 °C	
Temperature accuracy	± 0.8 °C ± 0.5 °C	With calibration
Column capacity	Three 30 cm	
Warm-up/cool-down time	5 minutes from ambient to 40 °C 10 minutes from 40 – 20 °C	
Dead volume	3 µL left heat exchanger 6 µL right heat exchanger	
Communications	Controller-area network (CAN), RS-232C, APG Remote: ready, start, stop and shut-down signals, LAN via other 1260 Infinity module	
Safety and maintenance	Extensive diagnostics, error detection and display (through Instant Pilot and Agilent data system), leak detection, safe leak handling, leak output signal for shutdown of pumping system. Low voltages in major maintenance areas.	
GLP features	Column-identification module for GLP documentation of column type.	
Housing	All materials recyclable	

### NOTE

All specifications are valid for distilled water at ambient temperature (25 °C), set point at 40 °C and a flow range from 0.2 –5 mL/min.

## Performance Specifications

**Table 2**    Performance Specifications Agilent 1260 Infinity High Performance Degasser

Type	Specification
Number of solvent channels	4
Flow range	0 – 10 mL/min per channel
Internal volume per channel	0.45 mL per channel
Materials in contact with solvent	TFE/PDD Copolymer, FEP, PEEK
pH range	1 – 14

## Performance Specifications G1314C

**Table 4** Performance Specifications G1314C

Type	Specification	Comments
Detection type	Double-beam photometer	
Light source	Deuterium lamp	
Wavelength range	190 – 600 nm	
Short term noise (ASTM)	$< \pm 0.5 \cdot 10^{-5}$ AU at 254 nm	See “ <a href="#">Specification Conditions</a> ” on page 29
Drift	$3 \cdot 10^{-4}$ AU/h at 254 nm	See “ <a href="#">Specification Conditions</a> ” on page 29.
Linearity	> 2 AU (5 %) upper limit	See “ <a href="#">Specification Conditions</a> ” on page 29.
Wavelength accuracy	$\pm 1$ nm	Self-calibration with deuterium lines, verification with holmium oxide filter
Maximum data rate	55 Hz	
Band width	6.5 nm typical	
Flow cells	Standard: 14 $\mu$ L volume, 10 mm cell path length and 40 bar (580 psi) pressure maximum High pressure: 14 $\mu$ L volume, 10 mm cell path length and 400 bar (5800 psi) pressure maximum Micro: 1 $\mu$ L volume, 5 mm cell path length and 40 bar (580 psi) pressure maximum Semi-micro: 5 $\mu$ L volume, 6 mm cell path length and 40 bar (580 psi) pressure maximum	Can be repaired on component level
Control and data evaluation	Agilent ChemStation for LC	

## 2 Site Requirements and Specifications

### Performance Specifications

**Table 4** Performance Specifications G1314C

Type	Specification	Comments
Analog outputs	Recorder/integrator: 100 mV or 1 V, output range 0.001 to 2 AU, one output	
Communications	Controller-area network (CAN), RS-232C, APG Remote: ready, start, stop and shut-down signals, LAN (optional)	
Safety and maintenance	Extensive diagnostics, error detection and display (through Agilent ChemStation), leak detection, safe leak handling, leak output signal for shutdown of pumping system. Low voltages in major maintenance areas.	
GLP features	Early maintenance feedback (EMF) for continuous tracking of instrument usage in terms of lamp burn time with user-settable limits and feedback messages. Electronic records of maintenance and errors. Verification of wavelength accuracy with built-in holmium oxide filter.	
Housing	All materials recyclable.	