

Specifications

Ceramic Top Hot Plate Specifications

Overall Dimensions	HP88854100	HP88854105	HP88857100	HP88857105	HP88850100	HP88850105
Width - in.(cm)	5.1 (13)	5.1 (13)	8.2 (20.8)	8.2 (20.8)	11.3 (28.8)	11.3 (28.8)
Height - in.(cm)	3.9 (9.8)	3.9 (9.8)	4.1 (10.5)	4.1 (10.5)	4.1 (10.5)	4.1 (10.5)
Depth - in.(cm)	10.2 (25.9)	10.2 (25.9)	14.2(36)	14.2(36)	17.2(43.8)	17.2(43.8)
Weight - lbs.(kg)	3.3 (1.5)	3.3 (1.5)	7.5 (3.4)	7.5 (3.4)	11.5 (5.2)	11.5 (5.2)
Top Plate Dimensions						
Width - in.(cm)	4.25 (10.8)	4.25 (10.8)	7.25 (18.4)	7.25 (18.4)	10.5 (26.7)	10.5 (26.7)
Height - in.(cm)	1.0 (2.5)	1.0 (2.5)	1.0 (2.5)	1.0 (2.5)	1.0 (2.5)	1.0 (2.5)
Depth - in.(cm)	4.25 (10.8)	4.25 (10.8)	7.25 (18.4)	7.25 (18.4)	10.5 (26.7)	10.5 (26.7)
Volts	100-120	220-240	100-120	220-240	100-120	220-240
Amps	4.4	1.6	12	4.4	13	6.0
Watts	540	384	1440	1056	1560	1440
Freq.	50/60	50/60	50/60	50/60	50/60	50/60
Phase	1	1	1	1	1	1
Max. Temp °C (°F)	540°C(1004°F)	540°C(1004°F)	540°C(1004°F)	540°C(1004°F)	400°C(752°F)	400°C(752°F)

Ceramic Top Stirrer Specifications

Overall Dimensions	S88854100	S88854105	S88857100	S88857105	S88850100	S88850105
Width - in. (cm)	5.1 (13)	5.1 (13)	8.2 (20.8)	8.2 (20.8)	5.1 (13)	5.1 (13)
Height - in. (cm)	3.9 (9.8)	3.9 (9.8)	4.1 (10.5)	4.1 (10.5)	4.1 (10.5)	4.1 (10.5)
Depth - in. (cm)	10.2 (25.9)	10.2 (25.9)	14.2(36)	14.2(36)	17.2(43.8)	17.2(43.8)
Weight - lbs. (kg)	5.0 (2.2)	5.0 (2.2)	9.0 (4.1)	9.0 (4.1)	13.0 (5.9)	13.0 (5.9)
Top Plate Dimensions						
Width - in. (cm)	4.25 (10.8)	4.25 (10.8)	7.25 (18.4)	7.25 (18.4)	10.5 (26.7)	10.5 (26.7)
Height - in. (cm)	1.0 (2.5)	1.0 (2.5)	1.0 (2.5)	1.0 (2.5)	1.0 (2.5)	1.0 (2.5)
Depth - in. (cm)	4.25 (10.8)	4.25 (10.8)	7.25 (18.4)	7.25 (18.4)	10.5 (26.7)	10.5 (26.7)
Volts	100-120	220-240	100-120	220-240	100-120	220-240
Amps	0.2	0.1	0.2	0.1	0.2	0.1
Watts	24	24	24	24	24	24
Freq.	50/60	50/60	50/60	50/60	50/60	50/60
Phase	1	1	1	1	1	1