

ARG6PV-VT65MLSTACKMED2



68" x 23.63" x 24.38" (H x W x D)

Stacked combination of ARG6PV all-refrigerator with antimicrobial silver ion handle and hospital grade 'green dot' cord and VT65MLBIMED2 manual defrost all-freezer for vaccine storage

Highlights:

Independent refrigerator and freezer storage in one slim-fitting footprint for space-challenged facilities

Intelligent microprocessor digital temperature controller for optimum temperature management

Powder-coated handle with naturally occurring silver ions to help reduce germ spread

Product Features:

| | |
|---|--|
| Space-saving design | Allows you to create a full refrigerator-freezer with independent controls in a slim-fitting footprint |
| Easy assembly | Unit ships in three boxes for customer to install the StackRack on the bottom refrigerator/freezer and place and secure the other unit on top |
| Antimicrobial silver ion-coated handle | Powder-coated handle with naturally occurring silver ions to help reduce the spread of germs |
| Purpose-built design | Designed and purpose-built for pharmacy, medication, and vaccine applications to support meeting CDC/VFC/VFA guidelines |
| +/-1°C Variation (refrigerator) | The published temperature variation is derived from the maximum deviation of an NTC sensor in a 1 oz. vial located nearest the chamber geometric center during a 24 hour test period |
| Adjustable temperature | Intuitive controls let you adjust the interior temperature between +2 to +8°C (refrigerator) and -20° to -15°C (freezer) |
| Temperature alarms | Visual and audible alarms alert if the interior temperature rises or falls out of set range |
| Remote alarm contacts (refrigerator) | Electronic controller is equipped with a volt-free contact for alarm forwarding to an external remote system (contacts located in the external rear of the unit) |
| Automatic defrost with adjustable cycle | Adjustable cycle defrost operation ensures the unit avoid temperature spikes and ice buildup |

ARG6PV-VT65MLSTACKMED2 Specifications:

| Overview | |
|-----------------------------------|--------------------|
| Nominal Height | 68.0" (173 cm) |
| Height of Cabinet | 68.0" (173 cm) |
| Nominal Width | 24.0" (61 cm) |
| Width | 23.63" (60 cm) |
| Nominal Depth | 25.0" (64 cm) |
| Depth | 24.38" (62 cm) |
| Depth with Handle | 26.13" (66 cm) |
| Capacity | 9.2 cu.ft. (261 L) |
| Door | Glass |
| Cabinet | White |
| US Electrical Safety | ETL |
| Canadian Electrical Safety | ETL-C |
| Voltage/Frequency | 115 V AC/60 Hz |
| Parts & Labor Warranty | 2 Years |
| Compressor Warranty | 5 Years |
| UPC | 761101065854 |
| Refrigerator-Freezer | |
| Door Swing | RHD |
| Reversible | Factory Reversible |
| Adjustable Shelves | Yes |
| Interior Light | Yes |
| Refrigerator - Interior Height | 24.5" (62 cm) |
| Refrigerator - Interior Width | 20.0" (51 cm) |
| Refrigerator - Interior Depth | 17.0" (43 cm) |
| Refrigerator - Capacity | 6.0 cu.ft |
| Refrigerator - Shelf Type | Wire |
| Refrigerator - Shelf Qty | 4 |
| Refrigerator - Temperature Range | 2 to 8°C |
| Refrigerator - Refrigerant Type | R600a |
| Refrigerator - Refrigerant Amount | 1.66 oz. |
| Freezer - Interior Height | 24.25" (62 cm) |
| Freezer - Interior Width | 17.63" (45 cm) |
| Freezer - Interior Depth | 17.0" (43 cm) |
| Freezer - Capacity | 3.2 cu.ft |
| Thermostat Type | Digital |

| | |
|------------------------------|---------------|
| Fan Type | Interior |
| Freezer - Temperature Range | -12° to -25°C |
| Freezer - Refrigerant Type | R134a |
| Freezer - Refrigerant Amount | 2.76 oz. |

