

MODEL 3750

| | |
|---------------------------------|--|
| Overall dimensions LxWxH | 16.25x14x5.75" (41.3x35.6x14.6cm) |
| Tray dimensions LxW | 13x11" (33x22.2cm) |
| Electrical | 120 volts, 5 amps, 40 watts 120 volts, 2.5 amps, 40 watts |
| Fuses | 5mm x 20mm, 5 amp quick acting |
| Speed Range | 20 to 300rpm |
| Speed Accuracy | |
| Above 100rpm | ±1% of set speed |
| Below 100rpm | ±1rpm |
| Orbit | 0.75" (19mm) Total Travel |
| Capacity | ~15 lbs @ 300rpm |
| Timer | 1 second to 160 hours |
| Controls | See page 6 |
| Ship Weight | 49lbs (22.2kg) |

MODEL 5000

| | |
|----------------------------------|--|
| Overall dimensions LxWxH | 23.6x26.7x6.0" (59.9x67.8x15.2cm) |
| Tray dimensions LxW | 18x24" (45.7x70cm) |
| Electrical | 120 volts, 5 amps, 75 watts 120 volts, 2.5 amps, 75 watts |
| Fuses | 5mm x 20mm, 5 amp quick acting |
| Speed Range (Advanced) | 20 to 500rpm |
| (Standard) | 25 to 500rpm |
| Speed Accuracy (Advanced) | |
| Above 100rpm | ±1% of set speed |
| Below 100rpm | ±1rpm |
| Orbit | 1" (25.4mm) |
| Capacity | ~50 lbs @ 125rpm ~10 lbs @ 500rpm |
| Timer (Advanced) | 1 second to 160 hours |
| (Standard) | 1 to 120 minutes |
| Controls (Advanced) | See page 6 |
| (Standard) | See page 5 |
| Ship Weight | 109lbs (49.4kg) |

MODEL 10000

| | |
|---------------------------------|--|
| Overall dimensions LxWxH | 28.25x26.7x7.0" (71.8x67.8x17.8cm) |
| Tray dimensions LxW | 24x24" (70x70cm) |
| Electrical | 120 volts, 5 amps, 80 watts 120 volts, 2.5 amps, 80 watts |
| Fuses | 5mm x 20mm, 5 amp quick acting |
| Speed Range | 10000-1 = 15 to 500rpm 10000-2 = 15 to 300rpm |
| Speed Accuracy | |
| Above 100rpm | ±1% of set speed |
| Below 100rpm | ±1rpm |
| Orbit | 15000-1 = 1" (25.4mm) 15000-2 = 2" (50.8mm) |
| Capacity | ~100 lbs @ 100rpm ~40 lbs @ 300rpm |
| Timer | 1 second to 160 hours |
| Controls | See page 6 |
| Ship Weight | 200lbs (90.7kg) |

MODEL 15000

| | |
|---------------------------------|--|
| Overall dimensions LxWxH | 28.25x36x7.0" (71.8x67.8x17.8cm) |
| Tray dimensions LxW | 24x36" (70x91.4cm) |
| Electrical | 120 volts, 5 amps, 80 watts 120 volts, 2.5 amps, 80 watts |
| Fuses | 5mm x 20mm, 5 amp quick acting |
| Speed Range | 15000-1 = 15 to 350rpm 15000-2 = 15 to 300rpm |
| Speed Accuracy | |
| Above 100rpm | ±1% of set speed |
| Below 100rpm | ±1rpm |
| Orbit | 15000-1 = 1" (25.4mm) 15000-2 = 2" (50.8mm) |
| Capacity | ~150 lbs @ 100rpm ~40 lbs @ 300rpm |
| Timer | 1 second to 160 hours |
| Controls | See page 6 |
| Ship Weight | 230lbs (104.3kg) |