

PRODUCT DATA SHEET

Published: 2026-03-17

LAUDA Universa U 8 E

Heating thermostat 200-240 V; 50/60 Hz

Part Number: L003968

Features

- Bath circulation thermostat for standard temperature control tasks up to 100 °C – reliable and intuitive to use.
- Future-proof thanks to modularity: LAUDA Universa with interchangeable control head and heating/cooling base allows flexible adaptation to current and future requirements.
- Bright VA LC display with clear two-line display and intuitive 3-button operation.
- Reliable circulation pump with flow reduction for adjusted volume flow and constant pressure.
- Integrated timer with countdown function for time-controlled temperature control processes.
- Intelligent remote control and monitoring: Integrated web server allows flexible remote control in the company network via the LAUDA Command app or browser-based, secured by PKI and 2-factor authentication. The connection to LAUDA.LIVE enables global, cloud-based data analysis and remote maintenance.
- Modern connectivity thanks to standard integrated Ethernet and USB interfaces for reliable data communication.
- Wireless communication: Integrated WLAN enables effortless connection with PC, tablet and smartphone.
- Proven safety features: low-level and overheating protection for operation with non-flammable liquids, audible and visual alarm signals.



Reserve technical changes

Options included

- Integrated Wi-Fi communication: The device may only be imported and used in certified countries and regions: United States of America, Canada, EU including the UK and Switzerland, and India.



Working temperature min.
35 °C



Working temperature max.
100 °C

PRODUCT DATA SHEET

Published: 2026-03-17

LAUDA Universa U 8 E


Heating thermostat 200-240 V; 50/60 Hz

Part Number: L003968

Technical Features

Working temperature range	35 ... 100 °C
Working temperature range with external cooling	20 ... 100 °C
Operating temperature range	-30 ... 100 °C
Ambient temperature range	5 ... 40 °C
Temperature stability	0.05 ± K
Heating capacity range	1.6 ... 2.2 kW
Power consumption max.	2.4 kW
Current max.	10 A
Size of bath (W x D x H)	150 x 150 x 200 mm
Bath opening (WxT)	150 x 150 mm
Bath volume min. / max.	6.6 / 8.8 L
Pump Pressure max.	0,2 bar
Pump flow rate max. (pressure)	15 L/min
Overall dimensions (WxDxH)	230 x 400 x 450 mm
Weight	10 kg
Power supply	200-240 V, 50/60 Hz
Power plug	Power cord with angled plug (CEE7/7)

Reserve technical changes



Power cord with angled plug (CEE7/7)


PRODUCT DATA SHEET

Published: 2026-03-17

LAUDA Universa U 8 E

Heating thermostat 200-240 V; 50/60 Hz

Part Number: L003968




PRODUCT DATA SHEET

Published: 2026-03-17

LAUDA Universa U 8 E

Heating thermostat 200-240 V; 50/60 Hz

Part Number: L003968



Reserve technical changes



JOINTLAB.COM

Jointlab S.r.l.

Via C. Treves 57, Trezzano sul Naviglio (Mi)

+39 0239310823 - info@frigolab.it