

Section 2 Specifications

Power Requirements

Model PR305225G:120 Volts, 50/60 Hz, 6.7 Amps, 800 Watts
Model PR305220G, PR305220GCN:240 Volts, 50/60 Hz, 3.3
Amps, 800 Watts

Overall Dimensions

Models PR305225G, PR305220G, PR305220GCN:18½"W x
13½"D x 22½"H (47 x 34 x 57 cm)

Chamber Dimensions

Models PR305225G, PR305220G, PR305220GCN: . . . 16"W x 11½"
D x 16-1/8"H (41 x 29 x 41 cm)

Volume

Models PR305225G, PR305220G, PR305220GCN: 1.7 cu. ft.
(48.2 liters)

Shipping Weight

Models PR305225G, PR305220G, PR305220GCN: . . .57 lbs. (26 kg)

Performance Characteristics

Temperature RangeAll models ambient +5°C to 210°C
Uniformity at 100°C±5.0°C
Control at 100°C±9.0°C

Environmental Operating Conditions

Pollution Degree*:2
Installation Category*:II
Altitude:2000 Meters MSL (Mean Sea Level)
Humidity:80% maximum, non-condensing
Electrical Supply:120VAC or 240VAC
Voltage Tolerance:±10% of normal rated line
Temperature:15°C to 40°C
Product Usage: This product is intended for use indoors only

**Refer to IEC 664-1*