

## 4 Technical Data

Parameter	Unit	2581	2585
<b>Pumping speed 50/60 Hz</b> at atmospheric pressure	m <sup>3</sup> / h	5.0 / 6,0	10.1 / 12.1
	l / min	83 / 100	168 / 201
<b>Ultimate pressure</b>	mbar	6.7	80
<b>Suction connection</b>	-	Hose nozzle DN 8 for hose inside diameter 8 mm	
<b>Pressure connection</b>		Hose nozzle DN 8 for hose inside diameter 8 mm and Exhaust silencer	
<b>Ambient temperature</b>	°C	+ 10 to + 40	
<b>Max. Operating gas temperature</b>		+ 60	
<b>Noise level</b> DIN EN ISO 2151	dB (A)	≤ 56	
<b>Voltage / Frequency</b>	V / Hz	230 / 50; 115 / 60	
<b>Motor power</b>	W	250	
<b>Type of protection</b> DIN EN 60529	-	IP 20	
<b>Weight</b>	kg	10.3	
<b>Dimensions (W/D/H)</b>	mm	432 / 191 / 305	
<b>Order No. for:</b>	-		
- <b>WOB-L® Piston pump</b> <b>230V, 50Hz</b> <i>inclusive mains connection cable with plug CEE</i>		<b>2581C-50</b>	<b>2585C-50</b>
- <b>WOB-L® Piston pump</b> <b>115V, 60Hz</b> <i>inclusive mains connection cable with plug US</i>		<b>2581B-50</b>	<b>2585B-50</b>

The information presented in this material is based on technical data and test results of nominal units. It is believed to be accurate and reliable and is offered as an aid to help in the selection of products.

It is the responsibility of the user to determine the suitability of the product for the intended use and the user assumes all risk and liability whatsoever in connection therewith.

Gardner Denver Thomas GmbH does not warrant, guarantee or assume any obligation or liability in connection with this information.