

IKA

designed for scientists



ICC control

/// Data Sheet

Compact immersion circulator ICC control for tempering of liquids up to 150 °C. Suitable to use in open or covered bath vessels.

The integrated pressure/ suction pump allow ICC control to be used for internal and external applications. Just connect the optional pump set. ICC control also has an optional cooling coil that allows to work close to ambient temperatures. The program function can save and run up to 10 individual procedures with 10 steps.

The ICC control circulator is first in its class with an integrated carrying handle that allows for comfortable transport and safe storage thanks to its clever stand.

The large, colour TFT screen offers intuitive controls of all process parameters.

www.ika.com

Subject to technical changes





designed for scientists

- Temperature range: RT - 150 °C
- Temperature stability: ± 0.01 K
- Powerful, speed-controlled pressure/suction pump
- Holding clamp for attaching the circulator to a bath, convenient carrying handle und integrated brackets
- Large easy to read TFT display for temperature, pump speed, filling level and safety temperature
- Programming function with 10 individual programs, each with 10 steps
- Adjustable safety circuit
- Connection for external PT 100 temperature probe
- Visual and acoustic safety warnings
- USB / RS 232 interface for PC control and documentation using labworldsoft®, as well as for online firmware updates

Scope of delivery

- Screwdriver
- USB Cable - USB A to Micro-B, 2 m



designed for scientists

Technical Data

| | |
|---|--------------------------------|
| Appliance type | Compact immersion circulators |
| Class designation acc. DIN 12876 | III |
| Identification according to DIN 12876 | FL |
| Heat output [W] | 2000 |
| Working temperature [°C] | room temp. +10K @1000rpm - 150 |
| Operating temperature min. (with external cooling) [°C] | -20 |
| Temperature display | yes |
| Temperature control | PID |
| Working temperature sensor | PT 100 |
| Safety temperature sensor | PT1000 |
| Working temperature display | TFT |
| Safety temperature display | TFT |
| Temperature stability DIN 12876 [K] | ±0.01 |
| Connection for ext. temperature sensor | PT 100 |
| Display resolution [K] | 0.01 |
| Display for operation with ext. sensor | yes |
| Set temperature resolution [K] | 0.1 |
| Warning function optical | yes |
| Warning function acoustic | yes |
| Warning function excess temperature | yes |
| Adjustable safety circuit [°C] | 0 - 160 |
| Sub-level protection | yes |
| Over-level protection | yes |
| Pump type | Pressure- / suction pump |
| Pump capacity adjustable | yes |
| Pump pressure max. (0 liters discharge flow) [bar] | 0.3 |
| Pressure pump (suction side) (0 liter flow) [bar] | 0.2 |
| Flow rate max. (0 bar back pressure) [l/min] | 18 |
| Bath depth min. [mm] | 150 |
| Calibration option | yes |
| Appliance fastener | clamp |
| Range of universal clamp [mm] | 0 - 40 |
| Technical data complies with the standard | DIN 12876 |
| Permissible ON time [%] | 100 |
| Dimensions (W x H x D) [mm] | 145 x 340 x 200 |
| Weight [kg] | 3.75 |
| Permissible ambient temperature [°C] | 5 - 40 |
| Permissible relative humidity [%] | 80 |
| Protection class according to DIN EN 60529 | IP 21 |
| RS 232 interface | yes |
| USB interface | Micro-USB |
| Voltage [V] | 230 |
| Frequency [Hz] | 50/60 |
| Power input [W] | 2100 |
| Batteries included with the product? | yes |
| Battery Cell Type | CR2032 |
| Number of Batteries | 1 |
| Battery Weight [g] | 3 |



designed for scientists

| | |
|-----------------------------|------------------|
| How is the Battery packaged | within appliance |
| Battery Energy Content [Wh] | 0.69 |
| Battery Voltage [V] | 3 |